



# Material Safety Data Sheet

## R-422D

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** R-422D  
**DISTRIBUTOR:** National Refrigerants, Inc.  
661 Kenyon Avenue  
Bridgeton, New Jersey 08302

**FOR MORE INFORMATION CALL:**  
(Monday-Friday, 8:00am-5:00pm)  
1-800-262-0012

**IN CASE OF EMERGENCY CALL:**  
CHEMTREC: 1-800-424-9300

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Pentafluoroethane (HFC-125)	354-33-6	65.1
1,1,1,2-Tetrafluoroethane (HFC-134a)	811-97-2	31.5
Isobutane (R-600a)	75-28-5	3.4

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

### 3. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW:** Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250 deg. C) decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides.

#### POTENTIAL HEALTH HAZARDS

**EYE:** Liquid contact can cause severe irritation and frostbite. Mist may irritate.

**SKIN:** Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.

**INGESTION:** Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

**INHALATION:** R-422D is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

**DELAYED EFFECTS:** None Known

Ingredients found on one of OSHA's designated lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
------------------------	-------------------	--------------------	------------------

No ingredients listed in this section



---

#### **4. FIRST AID MEASURES**

---

**SKIN:** Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

**EYES:** Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

**INHALATION:** Immediately remove to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention. Do not give epinephrine (adrenaline).

**INGESTION:** Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

**ADVICE TO PHYSICIAN:** Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

---

#### **5. FIRE FIGHTING MEASURES**

---

##### **FLAMMABLE PROPERTIES**

**FLASH POINT:** Gas, not applicable per DOT regulations

**FLASH POINT METHOD:** NA

**UPPER FLAME LIMIT (volume % in air):** NONE (per ASHRAE) Standard 34 with match ignition

**LOWER FLAME LIMIT (volume % in air):** NONE (per ASHRAE) Standard 34 with match ignition

**AUTOIGNITION TEMPERATURE:** Unknown for mixture

**FLAME PROPAGATION RATE (solids):** NA

**OSHA FLAMMABILITY CLASS:** NA

##### **EXTINGUISHING MEDIA:**

Use any standard agent—choose the one most appropriate for type of surrounding fire (material itself is not flammable)

##### **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

R-422D is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources. Contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and /or appropriate pressures).

##### **SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:**

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.



---

**6. ACCIDENTAL RELEASE MEASURES**

---

**IN CASE OF SPILL OR OTHER RELEASE:** (Always wear recommended personal protective equipment)  
Evacuate unprotected personnel. Protected personnel should remove ignition sources and shut off leak, if without risk, and provide ventilation. Unprotected personnel should not return until air has been tested and determined safe, including low-lying areas.

**Spill and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.**

---

**7. HANDLING AND STORAGE**

---

**NORMAL HANDLING:** (Always wear recommended personal protective equipment)

Avoid breathing vapors and liquid contact with eyes, skin or clothing. Do not puncture or drop cylinders, expose them to open flame or excessive heat. Use authorized cylinders only. Follow standard safety precautions for handling and use of compressed gas cylinders.

R-422D should not be mixed with air above atmospheric pressure for leak testing or any other purpose.

**STORAGE RECOMMENDATIONS:**

Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**ENGINEERING CONTROLS:**

Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operation and storage areas.

**PERSONAL PROTECTIVE EQUIPMENT**

**SKIN PROTECTION:**

Skin contact with refrigerant may cause frostbite. General work clothing and gloves (leather) should provide adequate protection. If prolonged contact with the liquid or gas is anticipated, insulated gloves constructed of PVA, neoprene or butyl rubber should be used. Any contaminated clothing should be promptly removed and washed before reuse.

**EYE PROTECTION:**

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear chemical safety goggles.

**RESPIRATORY PROTECTION:**

None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, or release into confined space, where the concentration may be above the PEL of 1,000 ppm, use a self-contained, NIOSH approved breathing apparatus or supplied air respirator. For escape, use the former or a NIOSH approved gas mask with organic vapor canister.



**ADDITIONAL RECOMMENDATIONS:**

Where contact with liquid is likely, such as in a spill or leak, impervious boots and clothing should be worn. High dose-level warning signs are recommended for areas of principle exposure. Provide eyewash stations and quick-drench shower facilities at convenient locations. For tank cleaning operations, see OSHA regulations, 29 CFR 1910.132 and 29CFR 1910.133.

**EXPOSURE GUIDELINES**

<b>INGREDIENT NAME</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>OTHER LIMITS</b>
Pentafluoroethane	None	None	*1000 ppm TWA (8hr)
1,1,1,2-Tetrafluoroethane	None	None	*1000 ppm TWA (8hr)
Isobutane	1000 ppm TWA (8hr)	None	None

\* = Workplace Environmental Exposure Level (AIHA).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>PHYSICAL STATE:</b>	Gas at ambient temperatures
<b>APPEARANCE:</b>	Clear, colorless liquid and vapor
<b>MOLECULAR WEIGHT:</b>	Mixture
<b>CHEMICAL FORMULA:</b>	CF <sub>3</sub> CHF <sub>2</sub> , CH <sub>2</sub> FCF <sub>3</sub> C <sub>4</sub> H <sub>10</sub>
<b>ODOR:</b>	Slight ethereal odor
<b>SOLUBILITY IN WATER (weight %):</b>	Not determined
<b>pH:</b>	Neutral
<b>BOILING POINT:</b>	-43deg.C (-46F)
<b>FREEZING POINT:</b>	Not determined
<b>VAPOR PRESSURE:</b>	147.24 psia @ 70 deg F    334.9 psia @ 130 deg. F
<b>VAPOR DENSITY (air = 1.0):</b>	3.0
<b>LIQUID DENSITY @ 1 atm:</b>	86.95 lb/ft <sup>3</sup>
<b>EVAPORATION RATE:</b>	>1 <b>COMPARED TO:</b> CCl <sub>4</sub> =1
<b>SPECIFIC GRAVITY (water = 1.0)</b>	1.15 @ 25 deg. C (77deg.F)
<b>% VOLATILES:</b>	100
<b>FLASH POINT:</b>	NA

**10. STABILITY AND REACTIVITY**

**NORMALLY STABLE? (CONDITIONS TO AVOID):**

Product is stable. Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

**INCOMPATIBILITIES:**

(Under specific conditions: e.g. very high temperatures and/or appropriate pressure)—Freshly abraded aluminum surfaces (may cause strong exothermic reaction). Chemically active metals: potassium, calcium, and powdered aluminum, magnesium and zinc.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Halogens, halogen acids and possibly carbonyl halides.



---

**HAZARDOUS POLYMERIZATION:**

Will not occur.

---

**11. TOXICOLOGICAL INFORMATION**

---

**IMMEDIATE (ACUTE) EFFECTS:**

HFC-125: LC50 : 4 hr. (rat) - > 800,000 ppm  
Cardiac Sensitization threshold (dog) 75,000 ppm.  
HFC-134a: LC50 : 4 hr. (rat) - > 500,000 ppm  
Cardiac Sensitization threshold (dog) 80,000 ppm.  
R-600a: LC50 : 15 min. (rat) - 570,000 ppm

**DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:**

HFC-125: Teratogenic NOEL (rat and rabbit) – 50,000 ppm  
Subchronic inhalation (rat) NOEL - >50,000 ppm  
Chronic NOEL – 10,000 ppm  
HFC-134a: Teratogenic NOEL (rat and rabbit) – 40,000 ppm  
Subchronic inhalation (rat) NOEL - 50,000 ppm  
Chronic NOEL – 10,000 ppm  
R-600a: Subchronic inhalation (rat) NOAEL - 4,489 ppm

**OTHER DATA:**

HFC-125, HFC-134a: Not active in four genetic studies  
R-600a: Negative Ames test with and without activation

---

**12. ECOLOGICAL INFORMATION**

---

**DEGRADABILITY (BOD):** R-422D is a gas at room temperature; therefore, it is unlikely to remain in water.

**Octanol Water Partition Coefficient:** Unknown for mixture

---

**13. DISPOSAL CONSIDERATIONS**

---

**RCRA**

**Is the unused product a RCRA hazardous waste if discarded?** Not a hazardous waste  
**If yes, the RCRA ID number is:** NA

**OTHER DISPOSAL CONSIDERATIONS:**

Disposal must comply with federal, state, and local disposal or discharge laws. R-422D is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.



The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

---

**14. TRANSPORT INFORMATION**

---

**US DOT PROPER SHIPPING NAME:** Liquefied gas, n.o.s., (1,1,1,2-tetrafluoroethane, Pentafluoroethane, Isobutane)  
**US DOT HAZARD CLASS:** 2.2  
**US DOT PACKING GROUP:** Not applicable  
**US DOT ID NUMBER:** UN3163

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

---

**15. REGULATORY INFORMATION**

---

**TOXIC SUBSTANCES CONTROL ACT (TSCA)**

**TSCA INVENTORY STATUS:** Components listed on the TSCA inventory  
**OTHER TSCA ISSUES:** Subject to Section 12(b) export notification. May contain 0-10 ppm Ethane, 2-chloro-1,1,1-trifluoro, CAS# 75-88-7

**SARA TITLE III / CERCLA:**

“Reportable Quantities” (RQs) and/or “Threshold Planning Quantities” (TPQs) exist for the following ingredients.

<u>INGREDIENT NAME</u>	<u>SARA / CERCLA RQ (lb.)</u>	<u>SARA EHS TPQ (lb.)</u>
No ingredients listed in this section		

**Spills or releases resulting in the loss of any ingredient at or above its RQ, requires immediate notification to the National Response Center (800) 424-8802 and to your Local Emergency Planning Committee.**

**SECTION 311 HAZARD CLASS:** IMMEDIATE, PRESSURE

**SARA 313 TOXIC CHEMICALS:**

The following ingredients are SARA 313 “Toxic Chemicals”. CAS numbers and weight percents are found in Section 2.

**INGREDIENT NAME**  
No ingredients listed in this section

**STATE RIGHT-TO-KNOW**

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

**INGREDIENT NAME**  
No ingredients listed in this section

**ADDITIONAL REGULATORY INFORMATION:**

R-422D is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

**WARNING:** Contains pentafluoroethane (HFC-125), tetrafluoroethane, and isobutane; greenhouse gases which may contribute to global warming

**Do not vent** to atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.



**WHMIS CLASSIFICATION (CANADA):**

This product has been evaluated in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by the CPR.

**FOREIGN INVENTORY STATUS:**

Australia	New Zealand
Europe	China
Canada	Japan
Korea	Philippines

---

**16. OTHER INFORMATION**

---

**CURRENT ISSUE DATE:** December, 2008

**PREVIOUS ISSUE DATE:** August, 2007

**OTHER INFORMATION:**

Regulatory Standards:

1. OSHA regulations for compressed gases: 29 CFR 1910.101
  2. DOT classification per 49 CFR 172.101
  3. ANSI /ASHRAE 34 Safety Group – A1
- Toxicity information per PAFT Testing, RTECS, HSDB, IUCLID

---

**17. DISCLAIMER**

---

National Refrigerants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods or use of the product and of the information referred to herein are beyond the control of National Refrigerants. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.